

Oilfield Solutions

Product Range

Imagine opening up new perspectives with the world's leading chemical company.

 **BASF**
The Chemical Company

Drilling

DRILLING	FUNCTION	CHEMISTRY	RECOMMENDED PRODUCTS
	Bentonite extenders	Polyacrylate, sodium salt	Alcomer® 180 Alcomer® 1771
	Biocides	Glutaraldehyde	Protectol® GA types Myacide®
	Cleaning agents	Alkylpolyglucosides, fatty alcohol alkoxyates	Basoclean™ types, Basosol™ types
	Corrosion inhibitors	Amine blends, ammonium derivatives, acetylene derivatives	Basocorr™ types
	Defoamers	Fatty alcohol alkoxyates	Basopur™ DF5
	Emulsifiers	Fatty alcohol alkoxyates	Basosol™ types
	Flocculants / Clean-up	Polyacrylamide-based polymers	Alcomer® 24 Alcomer® 80 types Alcomer® 90 types Alcomer® 700 types Alcomer® 7100 types Alcomer® 800 types
	Fluid loss additives	Sulfonated polymer, Polyacrylamide-based polymers	Polydrill® Alcomer® 242 Alcomer® 507
	Lubricants	Polyethylene glycol ester	Basoplur™ types Basotron™ KS1
	Shale inhibitors	Butanol alkoxyate Polyacrylamide-based polymers	Basodrill™ types Alcomer® 120 types Alcomer® 110RD Alcomer® 115 Alcomer® 60RD
	Thinners	Polyacrylate-based polymers	Polythin® Basogan™ DR 130 Alcomer® 74 L and 74
	Viscosifiers for WBM	Attapulgit Polyacrylamide-based polymers	DC-150 Alcomer® 120 types Alcomer® 130
	Viscosifiers for OBM	Polyacrylate-based polymers	Alcomer® 274 Alcomer® 275
	Wetting agents	Sulfosuccinate diester	Alcomer® D1235

Cementing

CEMENTING	FUNCTION	CHEMISTRY	RECOMMENDED PRODUCTS
	Dispersants	Polycarboxylate-based superplasticizers	Liquiment® 1641F and 5581F
		Polycondensate-based dispersants	Liquiment® F-10X and K2F
		The standard dispersant for oil well cementing	Liquiment® K3F
		Green dispersant	Liquiment® Bio
	Fluid loss control additives	Tailored blends for a variety of base applications	Polytrol® FL 29 and FL 32
	Fully synthetic polymers for demanding conditions	Polytrol® FL 34, FL 45 and Alcomer® 244	
Gas blocking additives	Polyethylenimine	Paragas®	
	Styrene-butadiene latices	Basoblock™ ND 614 and D 623	
Retarders	Fully synthetic retarder for demanding conditions	CemR-10	
Defoamers	Fatty alcohol alkoxyate	Basopur™ DF 5 and DF 9010 F	

Stimulation

STIMULATION	FUNCTION	CHEMISTRY	RECOMMENDED PRODUCTS
	Acids	Methanesulfonic acid	Baso MSA™
	Biocides	Glutaraldehyde	Protectol® Myacide® types
	Clean-up agents	Decanol ethoxylates	Basosol™ XP types
	Corrosion inhibitors	Acetylene derivatives	Basocorr™ types
	Friction reducers	Polyacrylamide-based polymers	Alcomer® 788 Alcomer® 889
	Gelling agents / Viscosifiers	Polyacrylamide-based polymers	Alcomer® 788 Alcomer® 889
	Non-emulsifiers	Alkoxyates	Basorol®
	Scale solvers	Amine-based oligo acetic acids	Basosolve™ types Baso MSA™
	Scale inhibitors	Polycarboxylates	Basogan™ types
	Water control polymers	Polycarboxylates, polyacrylamide-based polymers	Alcoflood® 254S Alcoflood® 955
	Wetting agents	Sulfosuccinate diester	Alcomer® D1235

Production

PRODUCTION	FUNCTION	CHEMISTRY	RECOMMENDED PRODUCTS
FLOW ASSURANCE	Pour point depressants	Modified polycarboxylates Polyacrylate/Polyvinylester blends	Basoflux® PI Basoflux® RD
	Scale inhibitors	Polycarboxylates	Basogan™, Basoscale™
	Scale solvers	Amine-based oligo acetic acids	Basosolve™
	Low dose gas hydrate inhibitors	Vinylcaprolactam-based polymers	Luvicap®
OIL / WATER SEPARATION	Demulsifiers	Resin alkoxyates, amine alkoxyates, polyethyleneimine alkoxyates, ethyleneoxide- propyleneoxide block copolymers	Basorol®
	Water clarifiers (Deoilers)	High molecular weight charged polymers	Alcomer® 7109, Alcomer® 216, Basomin™ SK, Basorol® RV
	Defoamers	Fatty alcohol alkoxyates	Basopur™ DF5
ASSET INTEGRITY	Corrosion inhibitors	Amine blends, ammonium derivatives	Basocorr™
	Cleaning agents	Alcohol alkoxyates, alkylpolyglucosides	Basoclean™, Basosol™
	H ₂ S scavengers	Glyoxal Triazine	Basolon™ GL 40 Basolon™ SC 78
	Biocide	Glutaraldehyde	Myacide®, Protectol®

The descriptions, designs, data and information contained herein are presented in good faith, and are based on BASF's current knowledge and experience. They are provided for guidance only, and do not constitute the agreed contractual quality of the product or a part of BASF's terms and conditions of sale. Because many factors may affect processing or application/use of the product, BASF recommends that the reader carry out its own investigations and tests to determine the suitability of a product for its particular purpose prior to use. It is the responsibility of the recipient of product to ensure that any proprietary rights and existing laws and legislation are observed. No warranties of any kind, either express or implied, including, but not limited to, warranties of merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth herein, or that the products, descriptions, designs, data or information may be used without infringing the intellectual property rights of others. Any descriptions, designs, data and information given in this publication may change without prior information. The descriptions, designs, data, and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the descriptions, designs, data or information given or results obtained, all such being given and accepted at the reader's risk. (09/2012)

® = registered trademark of BASF SE

North America

BASF Corporation

3120 Hayes Road
Houston, Texas 77082
Phone: +1 800 7941019
Fax: +1 877 2451806

South America

BASF S.A.

Avenida das Nações Unidas,
14.171 Morumbi
04794-000 São Paulo, Brazil
Phone: +55 11 2039-3482
Fax: +55 11 2039-2786

Europe

BASF SE

Oilfield Solutions
EV/EM-J542S
67056 Ludwigshafen
Phone: +49 621 60-56587
Fax: +49 621 60-6656587

Asia

BASF South East Asia Pte. Ltd.

#35-01 Suntec Tower One
7 Temasek Boulevard
038987 Singapore
Singapore
Phone: +65 6393-5208
Fax: +65 6430-9899

For further information:

oilfieldsolutions@basf.com, www.basf.com/oilfieldsolutions